

Polyfoam Joint Filler (30kg density)

A closed cell expanded polyethylene foam used for expansion joint in concrete slab construction and brickwork joints. Available in sheet form or cut to size with an option for 25mm rip-off strip for subsequent sealing.

Heavy Density 70kg also available



Code	Size mm
SPFS12	Polyfoam Sheet 12 x 2000 x 1600
SPFS20	Polyfoam Sheet 20 x 2000 x 1600
SPFS25	Polyfoam Sheet 25 x 2000 x 1600

Code	Slab Depth	Joint Thickness		
PF 100**	Metre	12mm	20mm	25mm
PF 150**	Metre	12mm	20mm	25mm
PF 175**	Metre	12mm	20mm	25mm
PF 200**	Metre	12mm	20mm	25mm

Bitumen Bonded Cork

Bitumen Bonded Cork joint filler board consists of granulated cork, premixed and securely bonded together with a hot bituminous mixture, evenly formed between two sheets of heavy asphalt – saturated paper. Recommended for use in concrete paved areas where heavy trafficking is expected.



Code	Sheet	Size		
BBCS**	0.914m x 2.134m	12mm	20mm	25mm

Code	Length	Joint Thickness		
BBC 150**	2.13m	12mm	20mm	25mm
BBC 175**	2.13m	12mm	20mm	25mm
BBC 200**	2.13m	12mm	20mm	25mm
BBC 225**	2.13m	12mm	20mm	25mm
BBC 250**	2.13m	12mm	20mm	25mm

**Denotes joint width.

Void Formers

A re-usable PVC void former for forming grooves in concrete, prior to sealing with joint sealant. Manufactured in 3 metre lengths. Available in full or half sections.



Code	Size
VF20H	3m x 20mm x 10mm
VF20F	3m x 20mm x 20mm
VF25H	3m x 25mm x 12mm
VF25F	3m x 25mm x 25mm

JOINT SEALANTS

Two Part Polysulphide Sealant

A high grade two part cold poured polysulphide sealant. Conforms to BS 4254. Supplied in a composite pack containing two separate components which, when mixed together, cure to form an elastic rubber. The material is supplied in either pouring grade for horizontal applications, or pouring grade for vertical applications.



Code	Item	Unit litres
GP5P	Pouring Grade	5.0
GP 25G	Gun Grade	2.5
JP 1	Primer	1.0

For prices please contact our sales office

Tel: 01223 862230 Fax: 01223 440246 Web: www.informuk.co.uk Email: general@informuk.co.uk

Joint Sealant (Pitch/Polyurethane)

A cold poured expansion joint sealant for roads and runways. Conforms to BS 5212.



To find the number of litres required:

$$\frac{\text{Joint width (mm)} \times \text{Joint depth (mm)}}{1000} \times \text{Joint length (metres)} = \text{Quantity (litres)}$$

Code	Unit Size litres
PJ	4.50
JP 1	1.00 Primer
JP 5	5.00 Primer

Polyurethane Sealant – One Part

A high movement elastomeric sealant supplied in 600cc foil containers ready for immediate use. It has been tested for use in contact with drinking water and has excellent adhesion properties when used in conjunction with Primer P.U. Should be used to seal expansion, contraction and construction joints in concrete reservoirs, water treatment works, pumping stations, sewage treatment works, canals and joints in brick/block construction.



Code	Item	Size
UF600	One Part	600cc
BG	Barrel/Gun	Each
TLC	Tool Cleaner	2.5 Ltrs
PUP	Primer P	1 Ltr

Supplied in foil containers for use with a Barrel Gun. Available in Black, Grey or White. DWI approved

Hot Pour Sealant

A hot poured Rubber Bitumen Joint Sealant manufactured from a blend of special bitumens, crumb rubber, SBS polymers, mineral fillers and extenders. Specifically developed for use as a joint sealant in concrete and asphalt pavements.



Code	Size
N2	20kg

Coverage: Linear metres per pack

10	161									
13	125	96.2								
15	108.7	84.8	72.5							
20	82	63.3	54.4	41						
25	66	50	43.9	32.7	26.2					
30	54.4	42	36.5	27.3	21.9	18.2				
35	47	36	31.3	23.4	18.8	15.7	13.4			
40	41	31.5	27.3	20	16.4	13.7	11.7	10.3		
45	36.5	28	24.3	18.2	14.6	12.2	10.4	9.2	8.1	
50	32.7	25.3	21.9	16.4	13.2	11	9.4	8.2	7.3	6.55
	10	13	15	20	25	30	35	40	45	50

Joint Width in Millimetres

Foam Backer Rod

Foam Backer Rod is a closed-cell cylindrical polyethylene cord for use as a back-up material for joint sealants. It is easily compressible with high recoverability and the cell structure also ensures that the material is non-absorbant.



Code	Item (dia. in mm)	Pack Size (meters per box)
SFBR10	10	1100
SFBR12	12	900
SFBR15	15	500
SFBR20	20	300
SFBR25	25	200
SFBR30	30	150
SFBR40	40	80
SFBR50	50	50