

PVC SPACER TUBES AND CONES

Spacer Tubes

Used as a distance spacer between formwork faces, they allow tie rods to be withdrawn for re-use. Available in 2m and 3m lengths.




Code	Internal Dia. mm	External Dia. mm	Weight Kg	No. in Pack
K22	22	26	0.184	50
K26	26	30	0.214	25
K32	32	36	0.285	25
K34	34	40	0.350	25
K40	40	46	0.470	25
K50	50	54	0.410	25
K106	106	110	1.200	25

Flexible Spacer Tube

Recommended for use when spacer tube needs to be recovered after concrete has been placed.

Supplied in 30 metre coils.



Code	Internal Dia mm	External Dia mm
FH19	19	25
FH26	26	31

Cones – Expendable

A wide range of single use plastic cones, for use with spacer tubes 22mm to 32mm diameter giving required concrete covers of 10mm, 12mm and 15mm.



Code	For Spacer Tube	Concrete Cover	No. in Pack	Weight Kg/1000
2210	K22	10mm	500	4.40
2215	K22	15mm	500	8.26
2612	K26	12mm	500	17.10
3212	K32	12mm	500	12.30

Cones – Re-usable

Manufactured from a rigid PVC, this range of cones can be extracted easily for re-use with the aid of a cone key. For use with spacer tubes 22mm to 40mm in diameter, giving concrete covers from 20mm to 50mm.



Code	For Spacer Tube	Concrete Cover	No. in Pack	Weight Kg/1000
2225	K22/26	25mm	500	16.60
2235	K22/26	35mm	250	21.48
2250EX	K22/26	50mm	250	29.75
2250	K22/26	50mm	125	25.00
2625	K26/30	25mm	250	15.84
2650	K26/30	50mm	125	26.00
3230	K32/36	30mm	250	28.52
4020	K40/46	20mm	125	20.00
CK		Cone Key		0.34

Plugs

An easy cost effective way of plugging the end of spacer tubes prior to making good.



Code	Item	No. in Pack	Weight Kg/1000
P20	Plug 20	1000	1.85
P22	Plug 22	1000	2.37
P26	Plug 26	1000	5.00
P32	Plug 32	500	4.45
P40	Plug 40	250	12.00